

**Winter and road service area
maintenance equipments —
Power system and related
controls —
Interchangeability and
performance requirements**

ICS 43.160

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSi
British Standards

National foreword

This British Standard is the UK implementation of EN 15431:2008.

The UK participation in its preparation was entrusted by Technical Committee B/513, Construction equipment and plant and site safety, to Panel B/513/-/16, Winter maintenance and road surface and maintenance equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 February 2008

© BSI 2008

ISBN 978 0 580 56158 0

Amendments/corrigenda issued since publication

Date	Comments

ICS 43.160

English Version

Winter and road service area maintenance equipments - Power system and related controls - Interchangeability and performance requirements

Matériels de viabilité hivernale et d'entretien des dépendances routières - Organes de puissance et commandes associées - Interchangeabilité et exigences de performance

Winterdienst- und Straßenbetriebsdienstausstattung - Antrieb und Steuerung von Anbaumaschinen - Anforderungen an Austauschbarkeit und Leistung

This European Standard was approved by CEN on 21 October 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents	page
Foreword	3
1 Scope	4
2 Normative references	4
3 Power System and related controls	5
3.1 Hydraulic system for municipal vehicles - Specifications	5
3.1.1 Drive of the oil pump.....	5
3.1.2 Hydraulic Circuits.....	5
3.1.3 Connection between the hydraulic system of the vehicle and the implements	5
3.1.4 Flow Rates.....	5
3.1.5 Pressure	5
3.1.6 Power.....	6
3.1.7 Capacity of the oil tank	6
3.1.8 Maximum oil temperature, cooling capacity test procedure	6
3.1.9 Line cross sections.....	8
3.1.10 Couplings and functions	9
3.1.11 Hydraulic Fluid.....	10
3.2 Mechanical Front-Mounted Power Take Off PTO, shaft profile and Performance.....	10
3.2.1 General	10
3.2.2 Profile A: $n = 540 \text{ min}^{-1}$ $P_{\text{max}} = 60 \text{ kW}$	10
3.2.3 Profile B: $n = 540 \text{ min}^{-1}$ or $n = 1\,000 \text{ min}^{-1}$ $P_{\text{max}} = 150 \text{ kW}$	10
3.2.4 Power take-off shaft profile.....	11
3.3 Electrical Connectors.....	13
3.3.1 Connector 24 V, 7 pins, at the front of the vehicle, socket design according to ISO 1185	13
3.3.2 Connector 12 V, 7 pins, at the front of the vehicle, socket design based on ISO 1724	14
3.3.3 Electrical Connectors in the cabine, 24 V, 3 pin	15
3.3.4 Electrical Connectors in the cabin, 12 V, 3 pin.....	16
Bibliography	18

Foreword

This document (EN 15431: 2008) has been prepared by CEN/TC 337/WG 3 "Interface between tools and vehicle", the secretariat of which is held by UNI-CUNA, under the direction of Technical Committee CEN/TC 337 "Winter maintenance and road service area maintenance equipment", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2008, and conflicting national standards shall be withdrawn at the latest by July 2008.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard : Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

1 Scope

This document applies to power systems equipped for the operation and able to drive implements and attachments such as snow ploughs and/or spreaders on winter service vehicles or mowers on road service area maintenance vehicles, equipped with front-mounting plates according to EN 15432.

The purpose of this standard is to ensure interchangeability of vehicles and implements. The minimum requirements on the performance and the components of the hydraulic system as well as the kind, the size and the location of the connecting elements between the vehicle and the implement are specified in this standard.

This standard does not deal with airport equipment.

This standard does not cover applications, where the implements need a continuous hydraulic oil flow exceeding 45 l/min.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references the latest edition of the referenced document (including any amendments) applies.

ISO 1185, *Road vehicles – Connectors for the electrical connection of towing and towed vehicles – 7-pole connector type 24 N (normal) for vehicles with 24 V nominal supply voltage*

ISO 1724, *Road vehicles – Connectors for the electrical connection of towing and towed vehicles – 7-pole connector type 12 N (normal) for vehicles with 12 V nominal supply voltage*

ISO 16028, *Hydraulic fluid power – Flush-face type, quick-action couplings for use at pressures of 20 MPa (200 bar) to 31,5 MPa (315 bar) – Specifications*

ISO 16844-2, *Road vehicles – Tachograph systems – Part 2: Recording unit, electrical interface*

3 Power System and related controls

3.1 Hydraulic system for municipal vehicles - Specifications

3.1.1 Drive of the oil pump

The oil pump shall be driven directly by the vehicle engine and independently from the vehicle drive train. A clutch or a coupling between the engine and the pump is permissible. A drive ratio between the engine and the pump is allowed.

3.1.2 Hydraulic Circuits

The hydraulic circuits must be open type circuits.

The hydraulic system consists in either one variable displacement pump or one or two constant pumps.

If there are two circuits, they shall provide flowrate and pressure independent at any working condition.

For each circuit there shall exist:

- one primary excess pressure protection device and
- one switching device for unpressurized circulation. Each circuit or both circuits together shall be equipped with an oil reservoir and a filter for protection of the hydraulic system.

3.1.3 Connection between the hydraulic system of the vehicle and the implements

Hydraulic connectors shall be ensured by the use of quick couplings, refer to 3.1.10.

3.1.4 Flow Rates

Nominal Flow Rate circuit No. 1: min. 20 l/min +/- 5 l/min at 75 % of the nominal engine speed (e.g. snow plough);

Nominal Flow Rate circuit No. 2: min. 40 l/min +/- 5 l/min at 75 % of the nominal engine speed (e.g. spreader).

3.1.5 Pressure

Pressure circuit No.1: min. 175 bar

Pressure circuit No.2: min. 200 bar at trucks with GVW ≤ 18 t

min. 250 bar at trucks with GVW > 18 t

3.1.6 Power

Minimum continuous power for both circuits: $P_{\min} = 16 \text{ kW}$ at trucks with GVW $\leq 18 \text{ t}$

$P_{\min} = 20 \text{ kW}$ at trucks with GVW $> 18 \text{ t}$

3.1.7 Capacity of the oil tank

The capacity of the oil tank shall be such that a removal by the implements up to 10 l shall not affect the ability of the hydraulic system to work properly.

3.1.8 Maximum oil temperature, cooling capacity test procedure

The cooling capacity of the hydraulic system for winter maintenance vehicles shall be at least 5 % of the minimum continuous power (see section 3.1.6). For road service area maintenance vehicles including summer operation the cooling capacity shall be at least 25 % of the minimum continuous power. If required, an oil cooler can be installed.

The cooling capacity shall be verified with a test, which is described in the following.


While executing the hydraulic system test in the hydraulic circuit 2, the difference between the hydraulic oil temperature in the oil tank and the ambient air temperature must not exceed $\Delta T = 50 \text{ K}$, i.e. with an ambient air temperature of $30 \text{ }^\circ\text{C}$, the hydraulic oil temperature in the oil tank must not exceed $80 \text{ }^\circ\text{C}$.

An adjustable restrictor for simulating the power loss shall be connected to the couplings of circuit 2. The restrictor should be adjusted to a value Δp , that gives a power absorption equivalent to 5 alternatively 25 % of the minimum continuous power at 75 % of the rated engine speed. During the test, a temperature difference between the hydraulic oil temperature in the oil tank and the ambient air temperature of $\Delta T = 50 \text{ K}$ must not be exceeded.

The oil temperature has to be measured at the outlet of the oil tank.

For testing the system, the fans of the hydraulic oil cooler – if installed - need to be engaged.

Test condition: ambient air temperature $25 \text{ }^\circ\text{C} \pm 10 \text{ }^\circ\text{C}$.



Key

X t [s]
Y T [°C]

Figure1 – Temperature rise over time

Table 1 – Minimum cooling capacity

	Cooling capacity [% of the minimum continuous power]	Max. ΔT [K]
Winter maintenance vehicle	5	50
Road service area maintenance vehicle (winter and summer use)	25	50

The test can be terminated, when the temperature gradient $(T_2 - T_1) / (t_2 - t_1)$ is less than 5 K / 20 min.

$$P = Q \times \Delta p \quad (1)$$

where

- P is the power according to the minimum continuous power (see section 3.1.6);
- Q is the volume flow of circuit 2 at 75% of the rated engine speed (max. volume flow when variable displacement pumps are being used);
- Δp is the adjusted pressure at the flow restrictor;

EN 15431:2008 (E)

T is the oil temperature at the outlet of the oil tank;

ΔT is the temperature difference between the hydraulic oil temperature in the oil tank and the ambient temperature;

t is the time.

EXAMPLE for calculating the Δp for the test, which has to be adjusted at the flow restrictor:

GVW of the truck e.g. 19 t ⊙ $P_{\min} = 20 \text{ kW}$ (3.1.6)

Rated engine speed e.g. 2 200 min^{-1} ⊙ 75 % of rated engine speed = 1 650 min^{-1}

Cooling capacity 5 % (winter maintenance vehicle) ⊙ 5 % of 20 kW = 1 kW

Cooling capacity 25 % (road service area maintenance vehicle) ⊙ 25 % of 20 kW = 5 kW

Calculation of the pressure at the flow restrictor: $\Delta p = P/Q$

E.g. Q = 45 l/min, P = 1kW ⊙ $\Delta p = 13,33 \text{ bar}$

E.g. Q = 45 l/min, P = 5kW ⊙ $\Delta p = 66,67 \text{ bar}$

With this value of Δp , the test has to be executed.

3.1.9 Line cross sections

Circuit 1 min. internal diameter 10 mm

Circuit 2 min. internal diameter 12 mm

Separate Return Line via filter min. internal diameter 18 mm

Un-pressurised Return Line min. internal diameter 10 mm

3.1.10 Couplings and functions

3.1.10.1 General

Standard for a winterservice vehicle are 4 couplings at the front of the vehicle to control i.e. the snow plough and 2 couplings (continuous flow) to drive i.e. the salt spreader.

3.1.10.2 Hydraulic circuit 1:

Table 2 – Couplings circuit 1

Circuit	Cell	Port	Symbol	Colour	Function	Size/Standard	
I	1	1		red	Implement lift	ISO 16028 size 12.5 (socket)	
		2		red	Implement lower		
	2	3		green	Move to the left		
		4		green	Move to the right		
	3	5		yellow	Available for additional function		
		6		yellow			
	4	7		blue	Available for additional function		
		8		blue			
			T (Separate return line)		black	Discharge to tank via filter	ISO 16028 size 19 (socket)

3.2.4 Power take-off shaft profile

Dimensions in millimetres




Figure 2 – PTO shaft

Table 4 – Dimensions PTO shafts

All dimensions in millimetres

Dimension	Symbol	Profile A based on ISO 500-3, Type 1	Profile B based on SAE J499a
Number of splines	<i>n</i>	6	6
Groove to end of shaft	<i>A</i>	38 ± 0,8	38 ± 0,3
Effective spline length and hardened portion	<i>B</i>	≥ 76	77
Chamfer	<i>C</i>	6 + 1	8,7 ± 0,2
Chamfer angle	<i>D</i>	30 ° ± 3 °	30 ° ± 5 °
Major diameter	<i>D_{EE}</i>	34,87 - 0,12	44,32 + 0,05
Form diameter	<i>D_{FE}</i>	≤ 30,0	-
Minor diameter	<i>D_{IE}</i>	29,0 ± 0,1	36,0 + 0,25
ID of groove	<i>E</i>	29,40 ± 0,1	37,21 + 0,13
Radius of groove	<i>R</i>	6,8 ± 0,25	8,3 + 0,3
Tooth thickness	<i>S</i>	8,51 min / 8,64 max	10,95 + 0,05
Power take-off shaft profile		1 3/8"	1 3/4"

3.3 Electrical Connectors

3.3.1 Connector 24 V, 7 pins, at the front of the vehicle, socket design according to ISO 1185

Table 5 – Functions front connector 24V

Pin #	Circuit #	Colour	Function/ circuit
1	31	White	Ground (24 V-)
2	58-L	Black	Front left-side marker light
3	L	Yellow	Turn signal light, left
4	54	Red	Dipped beam headlights*
5	R	Green	Turn signal light, right
6	58-R	Brown	Front right-side marker lights
7	54-G	Blue	Headlights – main beam*
* Function only available at vehicles without bulb warning indicator.			

3.3.2 Connector 12 V, 7 pins, at the front of the vehicle, socket design based on ISO 1724

Table 6 – Functions front connector 12V

Pin #	Circuit #	Colour	Function/ circuit
1	L	Yellow	Turn signal light, left
2	54	Red	Dipped beam headlights*
3	31	White	Ground (12 V-)
4	R	Green	Turn signal light, right
5	58-R	Brown	Front right-side marker lights
6	54-G	Blue	Headlights – main beam*
7	58-L	Black	Front left-side marker light
* Function only available at vehicles without bulb warning indicator.			

3.3.3 Electrical Connectors in the cabine, 24 V, 3 pin

Socket 24V (male), max. amperage $I = 15 \text{ A}$, Protection class IP54

Dimensions in millimetres




Figure 3– 24 V socket

Table 7 – 24 V socket

Pin	Function
82	Speed Signal
31 -	Ground (24V -)
15/30 +	Pos. (24V +)

The speed pulse output (Pin 82) is a pulse-gap modulated signal according to ISO 16844-2, connector contact number B7.

3.3.4 Electrical Connectors in the cabin, 12 V, 3 pin

Socket 12V (female), max. amperage I = 25 A, Protection class IP54

Dimensions in millimetres




Figure 4 – 12 V socket

Table 8 – 12 V socket

Pin	Function
82	Speed Signal
31 -	Ground (12V -)
15/30 +	Pos. (12V +)

The speed pulse output (Pin 82) is a pulse-gap modulated signal according to ISO 16844–2, connector contact number B7.

Bibliography

- [1] EN 15432:2008, Winter and road service area maintenance equipments - Front-mounted equipments – Interchangeability
- [2] EN 60529, Degrees of protection provided by enclosures (IP code) (IEC 60529:1989)
- [3] ISO 500-3:2004 Agricultural tractors – Rear-mounted power take-off types 1, 2 and 3 – Part 3: Main PTO dimensions and spline dimensions, location of PTO
- [4] SAE J 499a:1975, Parallel side splines for soft broached holes in fittings

blank

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.

Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001.

Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.

Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.

Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553.

Email: copyright@bsi-global.com.